



SAFETY DATA SHEET

Page : 1
Revised edition no : 0
Date : 6 / 12 / 2016
Supersedes : 0 / 0 / 0

Carbon dioxide

SDS_CO2



2.2 : Non-flammable, nontoxic gases

Warning



SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Carbon dioxide
SDS Nr : SDS_CO2
Chemical description : Carbon dioxide
CAS No : 124-38-9
EC No : 204-696-9
Index No : ---
Registration-No. : Listed in Annex IV / V REACH, exempted from registration.
Chemical formula : CO2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use. Test gas/Calibration gas. Purging. Laboratory use. Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Contact supplier for more information on uses.

1.3. Details of the supplier of the safety data sheet

Company identification : STEELMAN GASES PVT LTD
Rajkot Highway, Vill. Shekhpur
Surendranagar
info@steelmangas.com
www.steelmangas.com

1.4. Emergency telephone number

Emergency telephone number : +91 9825188035

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

Hazard Class and Category Code Regulation EC 1272/2008 (CLP)
• Physical hazards : Gases under pressure - Liquefied gas - Warning - (CLP : Press. Gas) - H280
Classification EC 67/548 or EC 1999/45 : Not classified as dangerous substance / mixture. Not included in Annex VI. No EC labelling required.

2.2. Label elements

Labelling Regulation EC 1272/2008 (CLP)
• Hazard pictograms





SAFETY DATA SHEET

Page : 1
Revised edition no : 0
Date : 6 / 12 / 2016
Supersedes : 0 / 0 / 0

Carbon dioxide

SDS_CO2

SECTION 2. Hazards identification (continued)

- Hazard pictograms code : GHS04
- Signal word : Warning
- Hazard statements : H280 - Contains gas under pressure; may explode if heated.
- Precautionary statements
- Storage : P403 - Store in a well-ventilated place.

2.3. Other hazards

: Asphyxiant in high concentrations. Contact with liquid may cause cold burns/frostbite.

SECTION 3. Composition/information on ingredients

3.1. Substance / 3.2. Mixture

Substance name	Contents	CAS No, EC No, Index No Registration no	Classification(DSD)	Classification(CLP)
Carbon dioxide	100 %	124-38-9,204-696-9 * 1	Not classified (DSD)	Press. Gas Liquefied (H280)

Contains no other components or impurities which will influence the classification of the product.

* 1: Listed in Annex IV / V REACH, exempted from registration.

* 2: Registration deadline not expired.

* 3: Registration not required: Substance manufactured or imported < 1t/y.

Full text of R-phrases see section 16. Full text of H-statements see section 16.

SECTION 4. First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/ consciousness. Victim may not be aware of asphyxiation. Low concentrations of CO2 cause increased respiration and headache.

4.3. Indication of any immediate medical attention and special treatment needed

: None.

SECTION 5. Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None.


5.3. Advice for fire-fighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible.

STEELMAN GASES PVT LTD.

Factory Add. Plot No.21, Survey No.-439/2,
Rajkot Highway, Vill.Shekhpar
Surendranagar

In case of emergency: +91 9825188035

	SAFETY DATA SHEET	Page : 1 Revised edition no : 0 Date : 6 / 12 / 2016 Supersedes : 0 / 0 / 0
Carbon dioxide		SDS_CO2

SECTION 5. Firefighting measures (continued)

Special protective equipment for fire fighters

: Use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

: Try to stop release. Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Prevent from entering sewers, basements and work pits, or any place where its accumulation can be dangerous.

6.2. Environmental precautions

: Try to stop release.

6.3. Methods and material for containment and cleaning up

: Ventilate area.

6.4. Reference to other sections

: See also sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Safe use of the product

: Only experienced and properly instructed persons should handle gases under pressure. The substance must be handled in accordance with good industrial hygiene and safety procedures. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not smoke while handling product. Ensure the complete gas system was (or is regularly) checked for leaks before use. Avoid suck back of water, acid and alkalis. Consider pressure relief device(s) in gas installations.

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions. Do not allow back feed into the container. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

STEELMAN GASES PVT LTD.

Factory Add. Plot No.21, Survey No.-439/2,
Rajkot Highway, Vill.Shekhpur
Surendranagar

In case of emergency: +91 9825188035

**SAFETY DATA SHEET**

Page : 1

Revised edition no : 0

Date : 6 / 12 / 2016

Supersedes : 0 / 0 / 0

Carbon dioxide**SDS_CO2****SECTION 7. Handling and storage (continued)****7.2. Conditions for safe storage, including any incompatibilities**

: Keep container below 50°C in a well ventilated place. Containers should be stored in the vertical position and properly secured to prevent toppling. Stored containers should be periodically checked for general condition and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Keep away from combustible materials.

7.3. Specific end use(s)

: None


SECTION 8. Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits
Carbon dioxide**

: Value 8h (CZ) [mg/m³] : 9000
: LTEL - UK [mg/m³] : 9150
: LTEL - UK [ppm] : 5000
: STEL - UK [mg/m³] : 27400
: STEL - UK [ppm] : 15000
: VME - France [mg/m³] : 9000
: VME - France [ppm] : 5000
: MAK (AU) Tagesmittelwert (ml/m³) : 5000
: TLV© -TWA [ppm] : 5000
: MAK (AU) Tagesmittelwert (mg/m³) : 9000
: MAK (AU) Kurzzeitwerte (ml/m³) : 10000
: MAK (AU) Kurzzeitwerte (mg/m³) : 18000
: TLV© -STEL [ppm] : 30000
: VLA-ED - Spain [ppm] : 5000
: VLA-ED - Spain [mg/m³] : 9150
: NGV - [ppm] : 5000
: NGV - [mg/m³] : 9000
: KTV - [ppm] : 10000
: KTV - [mg/m³] : 18000
: Grænserværdier (DK) (ppm) : 5000
: HTP-vården (FI) - 8 H - [ppm] : 5000
: HTP-vården (FI) - 8 H - [mg/m³] : 9100
: Grænserværdier (DK) mg/m³ : 9000
: Grenseverdi (NO) 8 timers [ppm] : 5000
: Grenseverdi (NO) 8 timers [mg/m³] : 9000
: TGG 8 uur (NL) (mg/m³) : 9000
: VME-CH [mg/m³] : 9000
: 8-Hour TWA (PL) (NDS) (mg/m³) : 9000
: 15-Minute STEL (PL)(NDSch) (mg/m³) : 27000
: Valori Limite di Soglia (IT) 8 ore [ppm] : 5000
: Valori Limite di Soglia (IT) 8 ore [mg/m³] : 9000
: TLV-TWA (Belgium) (ppm) : 5000
: TWA BE 8h [mg/m³] : 9131
: TLV-STEL (Belgium) (ppm) : 30000
: STEL BE 15min [mg/m³] : 54784
: Valoare limita maxima (RO) 8 ore [mg/m³] : 9000
: Valoare limita maxima (RO) 8 ore [ppm] : 5000
: TWA LT 8h [ppm] : 5000
: TWA LT 8h [mg/m³] : 9000
: TWA BG 8h [mg/m³] : 9000
: TWA EE 8h [ppm] : 5000
: TWA EE 8h [mg/m³] : 9000

STEELMAN GASES PVT LTD.

Factory Add. Plot No.21, Survey No.-439/2,
Rajkot Highway, Vill.Shekhpar
Surendranagar

In case of emergency: +91 9825188035

	SAFETY DATA SHEET	Page : 1 Revised edition no : 0 Date : 6 / 12 / 2016 Supersedes : 0 / 0 / 0
Carbon dioxide		SDS_CO2

SECTION 8. Exposure controls/personal protection (continued)

: TWA LV 8h [ppm] : 5000
: Value 15min. (CZ) [mg/m3] : 45000
: TWA LV 8h [mg/m3] : 9000
: TWA MT 8h [ppm] : 5000
: TWA MT 8h [mg/m3] : 9000
: TWA CY 8h [ppm] : 5000
: TWA CY 8h [mg/m3] : 9000
: No data available.

DNEL: Derived no effect level (Workers)

PNEC: Predicted no effect concentration

: No data available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

: Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit system e.g. for maintenance activities. Systems under pressure should be regularly checked for leakages. Ensure exposure is below occupational exposure limits (where available). Provide adequate general and local exhaust ventilation.

8.2.2. Individual protection measures, e.g. personal protective equipment

: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.

- **Eye/face protection**

: Wear safety glasses with side shields. Wear safety glasses with side shields or goggles when transfilling or breaking transfer connections. Standard EN 166 - Personal eye-protection.

- **Skin protection**

- Hand protection

: Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk.

- Other

: Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

- **Respiratory protection**

: Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

- **Thermal hazards**

: None necessary.

8.2.3. Environmental exposure Controls

: None necessary.

**SAFETY DATA SHEET**Page : 1
Revised edition no : 0
Date : 6 / 12 / 2016
Supersedes : 0 / 0 / 0**Carbon dioxide****SDS_CO2****SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	
Physical state at 20°C / 101.3kPa	: Gas.
Colour	: Colourless.
Odour	: No odour warning properties.
Odour threshold	: Odour threshold is subjective and inadequate to warn for overexposure.
pH value	: Not applicable.
Molar mass [g/mol]	: 44
Melting point [°C]	: -78.5
Boiling point [°C]	: -56.6 (s)
Critical temperature [°C]	: 30
Flash point [°C]	: Not applicable for gases and gas-mixtures.
Evaporation rate (ether=1)	: Not applicable for gases and gas-mixtures.
Flammability range [vol% in air]	: Non flammable.
Vapour pressure [20°C]	: 57.3 bar
Relative density, gas (air=1)	: 1.52
Relative density, liquid (water=1)	: 0.82
Solubility in water [mg/l]	: 2000 Completely soluble.
Partition coefficient n-octanol/water [log Kow]	: 0.83
Auto-ignition temperature [°C]	: Not applicable.
Viscosity at 20°C [mPa.s]	: Not applicable.
Explosive Properties	: Not applicable.
Oxidising Properties	: None.

9.2. Other information

Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
------------	--

SECTION 10. Stability and reactivity

10.1. Reactivity	: No reactivity hazard other than the effects described in sub-sections below.
10.2. Chemical stability	: Stable under normal conditions.
10.3. Possibility of hazardous reactions	: None.
10.4. Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
10.5. Incompatible materials	: None. For additional information on compatibility refer to ISO 11114.
10.6. Hazardous decomposition products	: None.

SECTION 11. Toxicological information**11.1. Information on toxicological effects**

Acute toxicity	: In high concentrations cause rapid circulatory insufficiency. Symptoms are headache, nausea and vomiting, which may lead to unconsciousness.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Reproductive toxicity	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas-mixtures.

STEELMAN GASES PVT LTD.Factory Add. Plot No.21, Survey No.-439/2,
Rajkot Highway, Vill.Shekhpar
Surendranagar**In case of emergency: +91 9825188035**

**SAFETY DATA SHEET**Page : 1
Revised edition no : 0
Date : 6 / 12 / 2016
Supersedes : 0 / 0 / 0**Carbon dioxide****SDS_CO2****SECTION 12. Ecological information**

- 12.1. Toxicity** : No ecological damage caused by this product.
12.2. Persistence and degradability : No ecological damage caused by this product.
12.3. Bioaccumulative potential : No ecological damage caused by this product.
12.4. Mobility in soil : No ecological damage caused by this product.
12.5. Results of PBT and vPvB assessment : Not classified as PBT or vPvB.
12.6. Other adverse effects
Effect on ozone layer : None.
Global warming potential [CO₂=1] : 1
Effect on the global warming : When discharged in large quantities may contribute to the greenhouse effect.

SECTION 13. Disposal considerations


- 13.1. Waste treatment methods** : Do not discharge into any place where its accumulation could be dangerous. May be vented to atmosphere in a well ventilated place. Discharge to atmosphere in large quantities should be avoided.
List of hazardous wastes : 16 05 05: Gases in pressure containers other than those mentioned in 16 05 04.
13.2. Additional information : None.

SECTION 14. Transport informationUN number : 1013
Labelling ADR, IMDG, IATA

2.2 : Non-flammable, nontoxic gases

- Land transport (ADR/RID)**
H.I. nr : 20
UN proper shipping name : CARBON DIOXIDE
Transport hazard class(es) : 2
Classification code : 2 A
Packing Instruction(s) : P200
Tunnel Restriction : C/E Tank carriage: Passage forbidden through tunnels of category C, D and E; Other carriage: Passage forbidden through tunnels of category E
Environmental hazards : None.
- Sea transport (IMDG)**
Proper shipping name : CARBON DIOXIDE
Class : 2.2
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-V
Packing instruction : P200
IMDG-Marine pollutant : No
- Air transport (ICAO-TI / IATA-DGR)**
Proper shipping name (IATA) : CARBON DIOXIDE
Class : 2.2
Passenger and Cargo Aircraft : Allowed.
Packing instruction - Passenger and Cargo Aircraft : 200
Cargo Aircraft only : Allowed.
Packing instruction - Cargo Aircraft Only : 200

STEELMAN GASES PVT LTD.Factory Add. Plot No.21, Survey No.-439/2,
Rajkot Highway, Vill.Shekhpar
Surendranagar**In case of emergency: +91 9825188035**

	SAFETY DATA SHEET	Page : 1 Revised edition no : 0 Date : 6 / 12 / 2016 Supersedes : 0 / 0 / 0
Carbon dioxide		SDS_CO2

SECTION 14. Transport information
Special precautions for user

: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers:

- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.
- Ensure there is adequate ventilation.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15. Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU legislation

Restrictions on use : None.

Seveso directive 96/82/EC : Not covered.

National legislation

National legislation : Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

: A CSA does not need to be carried out for this product.

SECTION 16. Other information
Indication of changes

: Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

Training advice

: The hazard of asphyxiation is often overlooked and must be stressed during operator training.

List of full text of H-statements in section 3.

: H280 - Contains gas under pressure; may explode if heated.

Further information

: This Safety Data Sheet has been established in accordance with the applicable European Union legislation.

DISCLAIMER OF LIABILITY

: Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Details given in this document are believed to be correct at the time of going to press. Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

End of document